



**TYPICAL WATER SERVICE PIPE AND
WATER SERVICE VALVE
MANIFOLD/TOBY**

NOTE:

1. ALL DIMENSIONS IN MILLIMETRES.
2. SERVICE TO BE LAID TO THE CENTRE OF THE FRONT PROPERTY BOUNDARY AND AT RIGHT ANGLES TO STREET BOUNDARY.
3. THE INSTALLATION IS TO UTILISE THE STANDARD MANIFOLD METER SYSTEM WITH THE DOUBLE CHECK AND STRAINER IN THE BODY OF THE MANIFOLD.
4. 100mm COMPACTED AP40 OR CEMENT STABILIZED FILL UNDER BOX
5. WHEN MANIFOLD AND BOX ARE INSTALLED WITHIN A VEHICLE CROSSING - WATER PIPE TAIL MUST BE INSTALLED FOR PLUMBER TO ACCESS



STANDARD DETAILS

**WATER SERVICE CONNECTIONS
TYPICAL CONNECTIONS WITH MANIFOLD**

Drawn	Designed	
J. GOODMAN	KCDC	
Approved	Revision Date	
B. MAGUIRE	OCTOBER 2020	
Scale	Drawing No.	Revision
NOT TO SCALE	HDC-WS-011	R0